

ROBIN[®] 600E Spot[™]

The ROBIN 600E Spot has a dramatically increased light output (from the 300 Series) and lower power requirements - thanks to an optimized optical path made from carefully selected components.



The super strong light-output can be maximised by using ROBE's unique HotSpot Control system together with the linear iris to create very powerful beam effects. An innovative patented cooling system ensures the best lamp operating temperatures and allows DMX controlled noise reduction. Users have complete control of all features of this fixture, making it ideal for environments where noise levels are critical and light output requirements are high.

Technical Specification

Source

- Lamp: Compact high-pressure metal halide lamp
- Base: PGJX28
- Approved model: Philips MSR Gold 575/2 MiniFastFit
- Control: Automatic and remote on/off
- Ballast: Electronic

Optical system

- Dichroic glass reflector for maximising the light efficiency
- Beam angle: Zoom range: 10° - 45° (2° - min. zoom with iris, 60° max. zoom with frost)

Electromechanical effects

- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- CTO: 0-100%
- Hot-spot control: Hot-or-not-spot
- Colour wheel: 7 replaceable "SLOT&LOCK" dichroic filters + open, trapezoid shape
- Static Gobo wheel: 9 replaceable "SLOT&LOCK" black and white gobos + open
- Rotating Gobo wheel: 7 rotating, indexable, replaceable "SLOT&LOCK" dichroic and glass gobos + openIris: Motorized, stepless, up to 3 Hz
- Prism: 3-facet 11° indexable prism rotating in both directions at different speeds
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobbing "ZAP"
- Motorized zoom and focus
- Pan: 540°
- Tilt: 280°

Control and programming

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 23, 25, 323 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC
- Pan/Tilt resolution: 8 or 16 bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Static gobo wheel positioning: 8 or 16bit
- Rotating gobos: 8 or 16bit
- Iris: 8 or 16bit
- Frost: 8 bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Built-in analyser for easy fault finding
- Optional wireless version available: CRMX™ technology from Lumen Radio

Static gobos

- Metal gobos - outside diameter: 26.9 mm, image diameter: 22.5 mm, aluminium, thickness: 0.5 mm
- Glass gobo - high temperature borofloat

Rotating gobos

- Glass gobos - outside diameter: 26.8 mm, image diameter: 22.0 mm, thickness: 1.1 mm, max. thickness: 4.0 mm, high temperature borofloat or better glass

Thermal specification

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 80 °C (176 °F)

Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 770 VA at 230 V/50 Hz

Mechanical specification


- Height: 516 mm (20.3 ") - head in horizontal position
- Width: 433 mm (17.0 ")
- Depth: 470 mm (18.5 ")
- Weight: 21.7 kg (47 lbs)
- Fixation option: Pan/Tilt-lock mechanism

Rigging

- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega bracket with ¼-turn quick locks
- Safety chain/rope attachment point

Gobos&Colours


Rotating Gobo Wheel



15020216




15020217




15020218



15020219



15020220




15020221



15030029

Colour Wheel



99011881




99011882



99011884



99011883



99011887



99011886



99011885

Static Gobo Wheel




15010734



15010720



15020222



15010735



15010728




15010730



15010736



15010737



15010738